


The STS 6010 is a programmable, fully automated, fuel maintenance system that removes water, sludge, and other contaminants from fuel storage tanks. Once installed, the STS 6010 system operates independently to ensure fuel reliability through routine fuel filtration. The system's fuel polishing process stabilizes diesel and bio-fuels, eliminates microbial contamination, and ensures fuel remains clean. The STS system's NEMA 4 rated enclosure allows for both outdoor and indoor installations by protecting the system from windblown dust and rain, hose directed water, and ice formations.



STS 6010 FEATURES:

Smart Filtration Controller Fully Automated and Programmable Operation Integration with External Monitoring Systems Unique Safety & Alarm Features Continuous-Duty Pump, Viton Seals System Upgrade Options

For safe operation, the STS 6010 is equipped with an automatic pump shut-down feature and alert indication to notify users of when the system requires servicing.

STS 6010 SPECIFICATIONS:

Nominal Flow	10 GPM/600 GPH (38 LPM/2,271 LPH)	
Rate Primary Filter	10 or 30μ Particulate or 60μ Stainless Steel Screen with Centrifugal Water Separator	
Secondary Filters	1, 3, 10 or 25μ Fine Filter or 3, 10μ Water Block	
Fuel Conditioner	LG-X 3000 Inline Magnetic Conditioner	
Pump	3/4 HP Spur Gear Pump	
System Controller	SFC70 Smart Filtration Controller with Safety and Alarm Features	
Power	120V/60Hz/1Ph or 230V/50Hz/1Ph*	
Plumbing	Black Iron	
Ports	1" NPT In, 1" NPT Out	
Enclosure Cabinet	NEMA 4 Rated Powder Coated or NEMA 4X Rated Stainless Steel	
Dimensions	≈ 37" x 60" x 12" (H x W x D)	
	(94 x 152 x 31 cm)	
Weight	≈ 513 lbs (233 kg)	
Not for use with fluids that have a flesh paint balance 4000F (27 00C)		

Not for use with fluids that have a flash point below 100°F (37.8°C).


*At 50 Hz, nominal flow rate decreases from 10 GPM to 8 GPM

REPLACEMENT FILTER OPTIONS:

Primary FilterPart No.Secondary Filters	Part No.
10μ Filter Cartridge010103μ Water Block Filter	WB-3
30μ Filter Cartridge*0103010μ Water Block Filter	WB-10
60μ Filter Cartridge01060S3μ Fine Filter*	FF-3
10μ Fine Filter	FF-10
25μ Fine Filter	FF-25
3μ X-Glass Media Fine Filter	FFZ-3

*Standard-issue filter element unless requested otherwise





- 1.Drain Valve
- 2. Water Collection Sump
 - 3. Water Detection Alarm Module
- 4.Fuel Inlet (From Tank)
- 5.Inlet Ball Valve
- 6. Vacuum Switch
- 7. Vacuum Gauge
 - 8. Primary Filter/Water Separator
- 9. Vacuum Switch
- 10.Motor with Coupled Gear Pump
- 11.Pressure Gauge
- 12.Pressure Switch
- 13. Fuel Conditioner
- 14.Smart Filtration Controller
- 15.Fuel Outlet (Discharge)
- 16.Outlet Ball Valve
- 17.Flow Switch
- 18. Fine Filters
- 19. Pressure Gauge
- 20. Pressure Switch (Not Visible)
- 21.Leak Detector

STS 6010 SYSTEM OPTIONS:

NEMA 4X RatedGain additional protection against corrosion with Enclosurea stainless steel enclosure

Manual Additive Manually draw additive into the polisher with a Injection dedicated supply port and ball valve

Enclosure HeaterPrevent the build up of condensation inside the system enclosure due to temperature changes

Auto Water Drain Automatically drain water separator of collected (AWD) water for decreased frequency of maintenance

Pressure Replace standard pressure switch for detailed

Transmittermonitoring of pressure levels in the system

Flow TransmitterReplace standard flow switch for detailed monitoring of flow rate in the system

Multi-Tank Polish and transfer fuel between multiple fuel Polishing/Transferstorage tanks

Fuel HeaterWarm up circulated fuel to resist gelling in freezing temperatures

System upgrade may be required for certain combinations of options -See controller specification sheet for more details

STS SYSTEM INTEGRATION:

