




Electronic Rocker Pedal 964 000 series

Characteristics

Each rocker pedal from the 964 000 series possesses the same features and guarantees:

- Two “built-in” return springs
- Die cast aluminum treadle support and mounting plate
- Water and dust ingress up to IP69K
- Storage temperature: -40°C to +125°C
- Operating temperature: -40°C to +85°C
- Connector: AMP – 6 pins

Output signal factory config

Output signal factory config.

The output values are factory programmable and hence can be adapted to the customer's specifications.

Analogue; PWM; IVS; Current; CAN J1939; CANopen

Standards

- FMVSS 124
 - FMVSS 302 (ECE R118)
 - 72/245/EEC
 - ECE R10.06*
 - E13 report
 - ISO 26262 part 5 – ASIL C (SEooC)*
- *only for APS Dual 5V and APS CAN sensors

Options

- Double sensors (up to 4 different signals available)
- Different treadle plates available
- Tilting plate
- CAN J1939
- Connector kit or customised wire harness

SALES CONTACT

CONTACT

✉ sales@rajkotmarinelc.ae
☎ +971 6 7487580
🌐 www.rajkotmarine.com

RAJKOT MARINE LLC

Jerf Industrial Area 1,
P.O Box 5861
Ajman, UAE

