



Electronic Throttle Pedal 965 000 series

Characteristics

The 965 000 series of electronic throttle pedals has various characteristics suitable for mobile equipment:

- Rest positions: 30°, 35° or 45°
- Travel angle: 18° or 22°
- Two “built-in” return springs
- Water and dust ingress up to IP69K
- Storage temperature: -40°C to +125°C
- Operating temperature: -40°C to +85°C
- Connector: AMP – 6 pin

Output signal factory config

The output values are factory programmable and hence can be adapted to the customer's specifications.

Analogue; PWM; IVS; Current; CAN J1939; CANopen

Standards

- FMVSS 124
 - FMVSS 302 (ECE R118)
 - 72/245/EEC
 - ECE R10.06*
 - E13 report
 - ISO 26262 part 5 – ASIL C (SEooC)*
- *only for APS Dual 5V and APS CAN sensors

Options

- Different treadle plates available
- Different mounting plates available
- Swivel arm
- Travel angle : 18° or 22°
- Mechanical kick-down
- CAN J1939
- Connector kit or customised wire harness

SALES CONTACT

CONTACT

✉ sales@rajkotmarinelc.ae
☎ +971 6 7487580
🌐 www.rajkotmarine.com

RAJKOT MARINE LLC

Jerf Industrial Area 1,
P.O Box 5861
Ajman, UAE

