



Electronic Throttle Position Sensor 979 000 series

Characteristics

The 979 000 series consists of efficient position sensors presenting various interesting features for machine industry and outdoor applications – similar and plug and play with the 974 000 series but with Polyamide housing:

- One return spring
- Travel angle: 42°
- PA66 GF30 housing
- Water and dust ingress up to IP69K
- Storage temperature: -40°C to +125°C
- Operating temperature: -40°C to +85°C
- Connector: AMP – 6 pins

Output signal factory config

The output values are factory programmable and hence can be adapted to the customer's specifications.

Analogue; PWM; IVS; Current; CAN J1939; CANopen

Standards

- FMVSS 124
 - FMVSS 302 (ECE R118)
 - 72/245/EEC
 - ECE R10.06*
 - E13 report
 - ISO 26262 part 5 – ASIL C (SEooC)*
- *only for APS Dual 5V and APS CAN sensors

Options

- Different levers available
- Two rotation senses available
- CAN J1939
- Connector kit or customised wire harness

SALES CONTACT

CONTACT

✉ sales@rajkotmarinelc.ae
☎ +971 6 7487580
🌐 www.rajkotmarine.com

RAJKOT MARINE LLC

Jerf Industrial Area 1,
P.O Box 5861
Ajman, UAE

